



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : DURA-KOTE GEL COAT REPAIR COLORS  
CAS No : mixture  
Product code : 314-XXX (GC)  
Formula : na

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : FIELD REPAIR GEL COAT

#### 1.3. Details of the supplier of the safety data sheet

Dura Technologies, Inc.  
2720 South Willow Avenue #A  
Bloomington, CA 92316

909.877.8477  
ChemTrec US: 800.424.9300  
ChemTrec Int: +1 70 3527 3887

#### 1.4. Emergency telephone number

Emergency number : ChemTrec US: 800.424.9300 Int: +1 70 3527 3887  
CHEMTREC: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Carc. Not classified	

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. Label elements

#### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P264 - Wash EXPOSED AREA. thoroughly after handling  
P280 - Wear eye protection, protective clothing, protective gloves  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P321 - Specific treatment (see SEEK MEDICAL AID. on this label)  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362 - Take off contaminated clothing and wash before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO2), dry chemical powder, foam to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/container to LOCAL, STATE, AND NATIONAL REGULATIONS.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Unsaturated Polyester Resin	(CAS No)TRADE SECRET	<= 33	Not classified
styrene, inhibited	(CAS No)100-42-5	<= 30	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351
talc	(CAS No)14807-96-6	<= 18	Not classified
titanium(IV) oxide	(CAS No)13463-67-7	<= 18	Carc. 2, H351
LEADS FREE COLOR DISPERSION	(CAS No)Proprietary	<= 2	Not classified
cobalt(II) 2-ethylhexanoate	(CAS No)136-52-7	<= 0.5	Carc. 2, H351

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: wash thoroughly for five minutes. seek medical attention. Get medical advice/attention. Specific treatment (see seek medical attention. on this label).
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: SEEK IMMEDIATE MEDICAL ATTENTION. Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause genetic defects (avoid skin contact and inhalation.). May cause cancer (avoid skin contact and inhalation.).
- Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor. Flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Reactivity : No reactivity hazard other than the effects described in sub-sections below.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Protective goggles. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing DUST, FUMES, MIST, OR VAPORS. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharge.
- Hygiene measures : Wash HANDS thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : HEAT SPARKS OR OPEN FLAMES. Keep in fireproof place. Keep container tightly closed.
- Incompatible products : Strong bases. strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heatsources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

styrene, inhibited (100-42-5)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH STEL (ppm)	40 ppm
talc (14807-96-6)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
titanium(IV) oxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure exposure is below occupational exposure limits (where available).
- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear approved mask.
- Other information : When using, do not eat, drink or smoke.

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: white.
Odor	: characteristic.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: $\geq 64$ °C
Flash point	: 30 - 34 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: $\geq 1.1$
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

#### 10.2. Chemical stability

Polymerization can result in formation of solid deposits, even in vapour space. Not established. Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture. Flammable liquid and vapor.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### DURA-KOTE GEL COAT ALL WHITE AND OFF WHITE( 1f )mixture

ATE CLP (vapors)	11.000 mg/l/4h
------------------	----------------

#### styrene, inhibited (100-42-5)

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 oral rat	5000 mg/kg (>6000 mg/kg bodyweight; Rat; Rat)
LD50 dermal rat	2820 mg/kg (>2000 mg/kg bodyweight; Rat; Rat; Experimental value)
LD50 dermal rabbit	5010 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	12 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	2770 ppm/4h (Rat)
ATE CLP (oral)	5000.000 mg/kg body weight
ATE CLP (dermal)	2820.000 mg/kg body weight
ATE CLP (gases)	2770.000 ppmV/4h
ATE CLP (vapors)	12.000 mg/l/4h
ATE CLP (dust, mist)	12.000 mg/l/4h

### titanium(IV) oxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 6.8 mg/l/4h (Rat; Experimental value,Rat; Experimental value)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.

### styrene, inhibited (100-42-5)

IARC group	2B - Possibly Carcinogenic to Humans
------------	--------------------------------------

### cobalt(II) 2-ethylhexanoate (136-52-7)

IARC group	2B - Possibly Carcinogenic to Humans
------------	--------------------------------------

### talc (14807-96-6)

IARC group	3 - Not classifiable
------------	----------------------

### titanium(IV) oxide (13463-67-7)

IARC group	2B - Possibly Carcinogenic to Humans
------------	--------------------------------------

Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Harmful if inhaled. Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### styrene, inhibited (100-42-5)

LC50 fish 1	25 mg/l (96 h; Lepomis macrochirus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	23 mg/l (48 h; Daphnia magna; LOCOMOTOR EFFECT)
LC50 fish 2	32 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 2	27 mg/l (24 h; Daphnia magna)
TLM fish 1	25.1 mg/l (96 h; Lepomis macrochirus; SOFT WATER)
TLM fish 2	46.4 mg/l (96 h; Pimephales promelas; SOFT WATER)

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>styrene, inhibited (100-42-5)</b>	
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit other aquatic organisms 1	10 - 100,96 h; Pseudomonas putida
Threshold limit other aquatic organisms 2	72 mg/l
Threshold limit algae 1	> 200 mg/l (192 h; Scenedesmus quadricauda; INHIBITORY)
Threshold limit algae 2	67 mg/l (Microcystis aeruginosa; INHIBITORY)

<b>talc (14807-96-6)</b>	
LC50 fish 1	> 100 g/l (24 h; Brachydanio rerio; INTERMITTENT FLOW)

<b>titanium(IV) oxide (13463-67-7)</b>	
LC50 fish 1	> 1000 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	< 1000 mg/l (432 h; Daphnia magna; Static system)
LC50 fish 2	> 1 g/l (96 h; Leuciscus idus)
EC50 Daphnia 2	< 500 mg/l (720 h; Daphnia magna; Static system)

### 12.2. Persistence and degradability

<b>DURA-KOTE GEL COAT ALL WHITE AND OFF WHITE(mixture)</b>	
Persistence and degradability	Not established.

<b>styrene, inhibited (100-42-5)</b>	
Persistence and degradability	Readily biodegradable in water. Not readily biodegradable in water. Forming sediments in water. Non degradable in the soil. Adsorbs into the soil. Photodegradation in the air. Not established.
Chemical oxygen demand (COD)	2.80 g O <sup>2</sup> /g substance
ThOD	3.07 g O <sup>2</sup> /g substance
BOD (% of ThOD)	0.42 % ThOD

<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
Persistence and degradability	Biodegradability in water: no data available.

<b>talc (14807-96-6)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

<b>Unsaturated Polyester Resin (TRADE SECRET)</b>	
Persistence and degradability	Not established.

<b>LEADS FREE COLOR DISPERSION (Proprietary)</b>	
Persistence and degradability	Not established.

<b>titanium(IV) oxide (13463-67-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### 12.3. Bioaccumulative potential

<b>DURA-KOTE GEL COAT ALL WHITE AND OFF WHITE(mixture)</b>	
Bioaccumulative potential	Not established.

<b>styrene, inhibited (100-42-5)</b>	
BCF fish 1	12 - 77 (QSAR)
BCF fish 2	35.5 (Carassius auratus)
Log Pow	2.95 - 3.16 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.

<b>cobalt(II) 2-ethylhexanoate (136-52-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Unsaturated Polyester Resin (TRADE SECRET)</b>	
Bioaccumulative potential	Not established.

<b>LEADS FREE COLOR DISPERSION (Proprietary)</b>	
Bioaccumulative potential	Not established.

<b>titanium(IV) oxide (13463-67-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.

### 12.4. Mobility in soil

<b>styrene, inhibited (100-42-5)</b>	
Surface tension	0.032 N/m (19 °C)

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to approved disposal site.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT) : UN1866

DOT Proper Shipping Name : RESIN SOLUTION

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

### Additional information

Other information : No supplementary information available.



# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### ADR

Transport document description : UN 1866, 3, III, (D/E)  
Packing group (ADR) : III  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code (ADR) : F1  
Danger labels (ADR) : 3 - Flammable liquids



Orange plates :



Tunnel restriction code : D/E  
LQ : 5L  
Excepted quantities (ADR) : E2

### Transport by sea

UN-No. (IMDG) : 1866  
Proper Shipping Name (IMDG) : RESIN SOLUTION  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : III - substances presenting low danger

### Air transport

UN-No. (IATA) : 1866  
Proper Shipping Name (IATA) : RESIN SOLUTION  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

styrene, inhibited (100-42-5)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Reactive hazard Fire hazard Delayed (chronic) health hazard

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Muta. 1B	H340
Carc. 1B	H350

Full text of H-phrases: see section 16

### Classification according to Directive 67/548/EEC or 1999/45/EC

Carc.Cat.2; R45  
Muta.Cat.2; R46  
F; R11  
Xn; R20  
Xi; R36/38

Full text of R-phrases: see section 16

### 15.2.2. National regulations

#### styrene, inhibited (100-42-5)

Listed on EPA's Hazardous Air Pollutants (HAPS)

### 15.3. US State regulations

#### DURA-KOTE GEL COAT ALL WHITE AND OFF WHITE(mixture)

State or local regulations	U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS) U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List«_STATE_OR_LOCAL_REGULATIONS&disp=value&t»
----------------------------	--

#### styrene, inhibited (100-42-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)

#### styrene, inhibited (100-42-5)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

## SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:


Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Carc. 2	Carcinogenicity Category 2
Carc. Not classified	Carcinogenicity Not classified
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer

# DURA-KOTE GEL COAT

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



### HMIS III Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 1 Slight Hazard
Personal Protection	: H

SDS US (GHS HazCom 2012)

*To the best of our knowledge this SDS is accurate. To the extent allowed by law, this statement is made in lieu of any other warranties, expressed or implied including but not limited to any implied warranty of merchantability or fitness for a particular purpose and is in lieu of any other obligations or liability on the part of Dura Technologies, Inc.*